THE DEAR TO

Dear Trackstar User:

Diamond Computer Systems, Inc. would like to welcome you as a new user of Trackstar.

- A. Our Customer Service Department has discovered that small amounts of RFI (Radio Frequency Interference) radiating from your monitor, when placed directly on the computer, may affect the performance of the Trackstar card. To avoid problems, please place a sheet of aluminum foil between the monitor and the top of the computer.
- B. If you are having problems running backed up Apple software on your Trackstar system, there may be a slight incompatibility problem between your MS DOS drive and the Apple compatible drive the very software was copied on. We suggest either using the original diskette or recopy the diskette in question on an Apple compatible drive that has had its speed and alignment checked recently.
- C. Some programs, mostly games, use half track copy protection which can not be accessed by any MD-DOS drives. To run these programs, you need to add an Apple compatible disk drive to your system.
- D. We are currently negotiating with Apple compatible disk drive manufacturer in order to provide you a quality drive at the lowest possible price. We have no intention to make a profit out of the disk drive. We see it as a service to our customers where the contract of the disk drive.

L'anite !

OF A OF

E. Your Trackstar was manufactured in the U.S.A. and packaged for educational and professional use only, in order to reduce the cost so that we can pass savings on to you.

Sincerely,

Ronald L. Morgan

Vice President for Engineering

Dear KAYPRO-TRACKSTAR user:

Here are some brief instructions on how to install your TRACKSTAR board in your KAYPRO computer:

- 1) Carefully remove the cover from your computer, remove the monitor cable from the video card, and remove the disk drive cable from the disk controller card (34-pin ribbon cable).
- 2) Install the TRACKSTAR board in slot #6.
- 3) Connect the supplied video cable from the monitor D9 connector, found on the back of the video card, to the IBM Molex pins on the TRACKSTAR board.
- 4) Install the disk drive cable from your disk drives to the 34-pin connector on the TRACKSTAR board. Pin #1 mark facing up.
- 5) Install the supplied disk drive cable from your disk controller card to the disk drive edge connector on the TRACKSTAR board.
- 6) If you have an Apple compatible disk drive connect it to the 20-pin ribbon cable connector. Pin #1 mark facing down.
- 7) Install your monitor cable to the D9 connector on the back of your TRACKSTAR board.
- 8) Replace your computer cover.

Sincerely,

Marty Mugno Technician